



# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/26/2017

Supersedes:01/14/2016

Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : TURBO 108 OCTANE BOOST 16 FL.OZ.  
Product code : NA30

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Octane Improver

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 4 H227  
Acute Tox. 3 (Oral) H301  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Eye Irrit. 2A H319  
Carc. 1B H350

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS06

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid  
H301 - Toxic if swallowed  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H350 - May cause cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P261 - Avoid breathing dust, fume, gas, mist, vapor spray  
P264 - Wash affected areas thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.  
P321 - Specific treatment: See section 4.1 on SDS  
P330 - Rinse mouth  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the : None under normal conditions.

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

classification

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Light	(CAS No) 64742-47-8	93 - 95	Asp. Tox. 1, H304
Tricarbonyl (methylcyclopentadienyl) Manganese	(CAS No) 12108-13-3	3 - 5	Acute Tox. 2 (Oral), H300 Acute Tox. 2 (Dermal), H310
1,2,4-Trimethylbenzene	(CAS No) 95-63-6	1 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
Naphtha, Heavy Aromatic	(CAS No) 64742-94-5	<= 1	Carc. 1B, H350 Asp. Tox. 1, H304
Naphthalene	(CAS No) 91-20-3	< 0.34	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-Methylnaphthalene	(CAS No) 91-57-6	< 0.26	Acute Tox. 4 (Oral), H302
1-Methylnaphthalene	(CAS No) 90-12-0	< 0.125	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302
Manganese Cyclopentadienyl Tricarbonyl	(CAS No) 12079-65-1	<= 0.1	Acute Tox. 2 (Oral), H300
Mesitylene	(CAS No) 108-67-8	<= 0.1	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411

The exact percentage is a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May cause cancer.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/injuries after skin contact	: Harmful in contact with skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the solid spill. Plug the leak, cut off the supply. Contain released substance, pump into suitable containers.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist, vapor spray. Obtain special instructions. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take off immediately all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations. Ground/bond container and receiving equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Distillates (Petroleum), Hydrotreated Light (64742-47-8)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm 8 Hours
Tricarbonyl (methylcyclopentadienyl) Manganese (12108-13-3)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (2-Methylcyclopentadienyl manganese tricarbonyl, as Mn; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-Methylnaphthalene (90-12-0)		
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm (1-methylnaphthalene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
2-Methylnaphthalene (91-57-6)		
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm (2-methylnaphthalene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Naphtha, Heavy Aromatic (64742-94-5)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup> 1-METHYLNAPHTHALENE
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm 1-METHYLNAPHTHALENE
1,2,4-Trimethylbenzene (95-63-6)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Manganese Cyclopentadienyl Tricarbonyl (12079-65-1)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (Manganese cyclopentadienyl tricarbonyl, as Mn; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Mesitylene (108-67-8)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.  
Personal protective equipment : Gloves. Avoid all unnecessary exposure. Safety glasses.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:  
Hand protection : Wear protective gloves.  
Eye protection : Chemical goggles or safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : Wear appropriate mask.  
Environmental exposure controls : Avoid release to the environment.  
Consumer exposure controls : Avoid contact during pregnancy/while nursing.  
Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Color : Light amber to dark amber.  
Odor : Mild . Hydrocarbon.  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : 161 °C  
Freezing point : No data available  
Boiling point : 106 °C  
Flash point : 93 °C  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : 141 mm Hg @ 21 deg C  
Relative vapor density at 20 °C : 4.5 Air=1  
Relative density : 0.86  
Solubility : Insoluble in water.  
Log Pow : No data available

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Inhalation:dust,mist: Harmful if inhaled.

<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h Based on lack of mortality and systemic effects
<b>Tricarbonyl (methylcyclopentadienyl) Manganese (12108-13-3)</b>	
LD50 oral rat	8 mg/kg (Rat)
LD50 dermal rat	665 mg/kg (Rat)
LD50 dermal rabbit	140 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	0.076 mg/l/4h (Rat)
<b>1-Methylnaphthalene (90-12-0)</b>	
LD50 oral rat	1840 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit; Literature study)
<b>2-Methylnaphthalene (91-57-6)</b>	
LD50 oral rat	1630 mg/kg (Rat)
<b>Naphthalene (91-20-3)</b>	
ATE CLP (oral)	500 mg/kg body weight
<b>Naphtha, Heavy Aromatic (64742-94-5)</b>	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat)
<b>1,2,4-Trimethylbenzene (95-63-6)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
<b>Manganese Cyclopentadienyl Tricarbonyl (12079-65-1)</b>	
LD50 oral rat	22 mg/kg (Rat)
<b>Mesitylene (108-67-8)</b>	
LD50 oral rat	6000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Read-across)

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Mesitylene (108-67-8)</b>	
LD50 dermal rat	> 2000 mg/kg bw/day (Rat; Read-across; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	24 mg/l/4h (Rat; Literature study)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: May cause cancer.

<b>Naphtha, Heavy Aromatic (64742-94-5)</b>	
IARC group	2B
National Toxicology Program (NTP) Status	3
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if inhaled. Toxic if swallowed.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/injuries after skin contact	: Harmful in contact with skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

<b>1-Methylnaphthalene (90-12-0)</b>	
LC50 fish 1	8.4 mg/l (LC50; 48 h; Salmo fario)
EC50 Daphnia 1	1.848 mg/l (LC50; 48 h)
LC50 fish 2	9 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 2	1.2 mg/l (EC50; 48 h)
Threshold limit algae 1	1.71 - 5.12, EC50; 3 h
Threshold limit algae 2	1200 µg/l (EC50; 14 days)

<b>2-Methylnaphthalene (91-57-6)</b>	
LC50 fish 1	8 mg/l (LC50; 96 h)

<b>Naphtha, Heavy Aromatic (64742-94-5)</b>	
EC50 Daphnia 1	0.95 mg/l (EC50; 48 h)
LC50 fish 2	2.34 mg/l (LC50; 96 h; Oncorhynchus mykiss)
Threshold limit algae 2	2.5 mg/l (EC50; 72 h)

<b>1,2,4-Trimethylbenzene (95-63-6)</b>	
LC50 fish 1	7.72 mg/l (LC50; 96 h; Pimephales promelas; Flow-through system; Fresh water)
EC50 Daphnia 1	3.6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 2	2.356 mg/l (EC50; ECOSAR; 96 h; Algae; Fresh water)

<b>Mesitylene (108-67-8)</b>	
EC50 Daphnia 1	6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 2	25 mg/l (EC50; DIN 38412-9; 48 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

<b>TURBO 108 OCTANE BOOST 16 FL.OZ.</b>	
Persistence and degradability	May cause long-term adverse effects in the environment. Not established.

<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Persistence and degradability	Not established.

<b>Tricarbonyl (methylcyclopentadienyl) Manganese (12108-13-3)</b>	
Persistence and degradability	Biodegradability in water: no data available.

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-Methylnaphthalene (90-12-0)</b>	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Not established.
<b>2-Methylnaphthalene (91-57-6)</b>	
Persistence and degradability	Inherently biodegradable. Not readily biodegradable in water. Not established.
<b>Naphthalene (91-20-3)</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.
<b>Naphtha, Heavy Aromatic (64742-94-5)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>1,2,4-Trimethylbenzene (95-63-6)</b>	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air. May cause long-term adverse effects in the environment.
Chemical oxygen demand (COD)	0.44 g O <sub>2</sub> /g substance
<b>Manganese Cyclopentadienyl Tricarbonyl (12079-65-1)</b>	
Persistence and degradability	Biodegradability in water: no data available.
<b>Mesitylene (108-67-8)</b>	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorption to soil is possible. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.0957 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.319 g O <sub>2</sub> /g substance
ThOD	3.19 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.03

### 12.3. Bioaccumulative potential

<b>TURBO 108 OCTANE BOOST 16 FL.OZ.</b>	
Bioaccumulative potential	Not established.
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Bioaccumulative potential	Not established.
<b>Tricarbonyl (methylcyclopentadienyl) Manganese (12108-13-3)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>1-Methylnaphthalene (90-12-0)</b>	
BCF fish 1	20 (BCF; 5 weeks)
BCF fish 2	113-2000,BCF; 1 - 2 weeks
Log Pow	3.87 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
<b>2-Methylnaphthalene (91-57-6)</b>	
BCF fish 1	407 (BCF; 624 h; Lepomis macrochirus)
BCF fish 2	190 (BCF; 840 h; Oncorhynchus kisutch)
Log Pow	3.86 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
<b>Naphthalene (91-20-3)</b>	
Bioaccumulative potential	Not established.
<b>Naphtha, Heavy Aromatic (64742-94-5)</b>	
Log Pow	2.9 - 6.1
Bioaccumulative potential	Bioaccumable.
<b>1,2,4-Trimethylbenzene (95-63-6)</b>	
BCF fish 1	31 - 275 (BCF; Other; 8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
<b>Manganese Cyclopentadienyl Tricarbonyl (12079-65-1)</b>	
Log Pow	-0.57 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.
<b>Mesitylene (108-67-8)</b>	
BCF fish 2	161 (BCF)
Log Pow	3.42 - 4.13 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-Methylnaphthalene (90-12-0)</b>	
Log Koc	Koc,2300
<b>1,2,4-Trimethylbenzene (95-63-6)</b>	
Surface tension	0.029 N/m
Log Koc	log Koc,3.04; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
<b>Mesitylene (108-67-8)</b>	
Surface tension	0.028 N/m
Log Koc	log Koc,2.87; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not Regulated,  
ICAO/IATA (air): Not Regulated,  
IMO/IMDG (water): Not Regulated,

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not Regulated

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>TURBO 108 OCTANE BOOST 16 FL.OZ.</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
<b>Naphthalene (91-20-3)</b>	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard
<b>Naphtha, Heavy Aromatic (64742-94-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	14 % Naphthalene (CAS 91-20-3)

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 1,2,4-Trimethylbenzene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

### CANADA

#### TURBO 108 OCTANE BOOST 16 FL.OZ.

WHMIS Classification Class B Division 3 - Combustible Liquid

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

#### Naphthalene (91-20-3)

WHMIS Classification Class B Division 4 - Flammable Solid  
Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

#### Naphtha, Heavy Aromatic (64742-94-5)

#### 1,2,4-Trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class B Division 3 - Combustible Liquid  
Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects  
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

## EU-Regulations

### 1,2,4-Trimethylbenzene (95-63-6)

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

T; R23/25

Xn; R21

R52/53

Full text of R-phrases: see section 16

### 15.2.2. National regulations

#### Naphtha, Heavy Aromatic (64742-94-5)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Canadian NDSL (Non-Domestic Substances List)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

#### 1,2,4-Trimethylbenzene (95-63-6)

## 15.3. US State regulations

#### TURBO 108 OCTANE BOOST 16 FL.OZ.

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - California - Proposition 65 U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Tricarbonyl (methylcyclopentadienyl) Manganese (12108-13-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>1-Methylnaphthalene (90-12-0)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>2-Methylnaphthalene (91-57-6)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Naphthalene (91-20-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	
<b>Naphtha, Heavy Aromatic (64742-94-5)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	Yes	Yes	
<b>1,2,4-Trimethylbenzene (95-63-6)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Manganese Cyclopentadienyl Tricarbonyl (12079-65-1)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Mesitylene (108-67-8)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Naphthalene (91-20-3)</b>				
<b>State or local regulations</b>				
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - California - Proposition 65				
<b>Naphtha, Heavy Aromatic (64742-94-5)</b>				
<b>State or local regulations</b>				
U.S. - California - Proposition 65 Illinois Right to Know Louisiana Right to Know Michigan Right to Know Minnesota Right-to-Know				

# TURBO 108 OCTANE BOOST 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Naphtha, Heavy Aromatic (64742-94-5)

New Jersey Right-to-Know  
U.S. - Pennsylvania - RTK (Right to Know) List  
Rhode Island Right to Know

### SECTION 16: Other information

Indication of changes : Revision - See : \*

Other information : None.


Full text of H-phrases:

H226	Flammable liquid and vapor
H227	Combustible liquid
H300	Fatal if swallowed
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H310	Fatal in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*